

Specification:

	Singemode(UPC)	Singemode(APC)	Multimode
Insertion loss	≤ 0.2db	≤ 0.2db	≤ 0.25db
Return loss	≥55db	≥65db	≥30db
Durability	≤ 0.1db typical change, 1000 times mating		
Operating Temperature	-45 to +85 degree		
Ferrule Hole Sizes	125.0+1/-0um, Concertricity: ≤1.0um	125.0+1/-0um, Concertricity: ≤0.5um	125.0um, Concertricity: ≤3.0um
	125.3+1/-0um, Concertricity: ≤1.0um	125.3+1/-0um, Concertricity: ≤0.5um	127.0um, Concertricity: ≤3.0um
	125.5+1/-0um, Concertricity: ≤1.0um	125.5+1/-0um, Concertricity: ≤0.5um	128.0um, Concertricity: ≤3.0um
	126.0+1/-0um, Concertricity: ≤1.0um	126.0+1/-0um, Concertricity: ≤0.5um	

Order Information:

Item	Connector Description	Item	Connector Description
	PC/UPC/APC		PC/UPC/APC
Connector Singlemode 9/125	ST	Connector Multimode (50/125 or 62.5/125)	ST
	SC		SC
	FC		FC
	LC		LC
	MU		MU
	MTRJ(female)		MTRJ(female)
	MTRJ(male)		MTRJ(male)
	DIN		