

Specification:

Descriptions	SM(PC)	SM(UPC)	SM(APC)	MM(PC)
Insertion loss	<0.3dB	≤0.2dB	<0.3dB	<0.3dB
Return loss	≥50dB	≥50dB	≥65dB	≥35dB
Repeatability	≤0.1	≤0.1	≤0.1	≤0.1
Durability	<0.1dB typical change,1000 mating			
Interchangeability	≤0.2dB			
Vibration	≤0.2dB			
Operating Temperature	- 20°C ~ + 70°C			
Storage Temperature	- 40°C ~ + 80°C			
Cable Diameter	3.0mm, 2.0mm, 0.9mm			

Order Information:

LC/UPC-SC/UPC-SM-SX-2.0mm-3M														
LC	/	UPC	—	SC	/	UPC	/	SM	—	SX	/	2.0	—	3M
1		2		3		2		4		5		6		7
1	Connector#1: LC,SC,FC,ST,DIN,D4,MU,MTRJ,etc.													
2	Lapping Way: UPC&APC (For MTRJ, F=Female, M=Male)													
3	Connector#2: LC,SC,FC,ST,DIN,D4,MU,MTRJ,Pigtail,etc.													
4	Cable Type: SM(9/125μm) ,MM(50/125μm & 62.5/125μm), OM3, OM4													
5	Fiber Number: SX(Simplex) or DX(Duplex), 2/4/6/8 core...													
6	Cable Diameter: 2.0=Ø2.0mm, 3.0=Ø3.0mm, 0.9=Ø0.9mm, etc.													
7	Cable Length: 3m(Length in meter)													