

Specification:

Item	Singlemode		Multimode
Splicing Type	UPC	APC	PC
Insertion Loss	$\leq 0.3\text{dB}$	$\leq 0.2\text{dB}$	$\leq 0.3\text{dB}$
Return Loss	$\geq 45\text{dB}$	$\geq 55\text{dB}$	$\geq 35\text{dB}$
Repeatability	$\leq 0.1\text{dB}$	$\leq 0.1\text{dB}$	$\leq 0.1\text{dB}$
Temperature	$-40/+80^{\circ}\text{C}$		

Order Information:

fibre Optic Patch Cord					
Connector Type	Ceramic Ferrule End Face	Cable Diameter (mm)	Simplex/Duplex	Single mode /Multi-mode	Length (meter)
FC	PC/UPC/APC	$\Phi 0.9, \Phi 2, \Phi 3$	Simplex/Duplex	SM/MM	Customized
SC	PC/UPC/APC	$\Phi 0.9, \Phi 2, \Phi 3$	Simplex/Duplex	SM/MM	Customized
ST	PC/UPC	$\Phi 0.9, \Phi 2, \Phi 3$	Simplex/Duplex	SM/MM	Customized
LC	PC/UPC	$\Phi 0.9, \Phi 2, \Phi 3$	Simplex/Duplex	SM/MM	Customized
MU	PC/UPC	$\Phi 0.9, \Phi 2$	Simplex/Duplex	SM/MM	Customized
MTRJ	PC/UPC	$\Phi 0.9, \Phi 2$	Duplex	SM/MM	Customized