

Specification:

	Fiber Count	Tubes	Fillers	Cable Diameter (mm)	Cable Weight (kg/km)	Tensile Strength (N)	Crush Resistance (N/100mm)	Bending Radius (mm)
						Long/Short Term	Long/Short Term	Static/Dynamic
GYTA-2~6	2~6	1	4	9.7	90	600/1500	300/1000	10D/20D
GYTA-8~12	8~12	2	3	9.7	90	600/1500	300/1000	10D/20D
GYTA-14~18	14~18	3	2	9.7	90	600/1500	300/1000	10D/20D
GYTA-20~24	20~24	4	1	9.7	90	600/1500	300/1000	10D/20D
GYTA-26~30	26~30	5	0	9.7	90	600/1500	300/1000	10D/20D
GYTA-32~36	32~36	6	0	10.2	104	1000/3000	300/1000	10D/20D
GYTA-38~48	38~48	4	1	11	117	1000/3000	300/1000	10D/20D
GYTA-50~60	50~60	5	0	11	117	1000/3000	300/1000	10D/20D
GYTA-62~72	62~72	6	0	11.5	126	1000/3000	300/1000	10D/20D
GYTA-74~84	74~84	7	1	13.4	154	1000/3000	300/1000	10D/20D
GYTA-86~96	86~96	8	0	13.4	154	1000/3000	300/1000	10D/20D
GYTA-98~108	98~108	9	1	14.8	185	1000/3000	300/1000	10D/20D
GYTA-110~120	110~120	10	0	14.8	185	1000/3000	300/1000	10D/20D
GYTA-122~132	122~132	11	1	16.9	228	1000/3000	300/1000	10D/20D
GYTA-134~144	134~144	12	0	16.9	228	1000/3000	300/1000	10D/20D