

**Specification:**

	<b>Singemode(UPC)</b>	<b>Singemode(APC)</b>	<b>Multimode</b>
<b>Insertion loss</b>	≤ 0.2db	≤ 0.2db	≤ 0.25db
<b>Return loss</b>	≥55db	≥65db	≥30db
<b>Durability</b>	≤ 0.1db typical change, 1000 times mating		
<b>Operating Temperature</b>	-45 to +85 degree		
<b>Ferrule Hole Sizes</b>	125.0+1/-0um, Concertricity: ≤1.0um	125.0+1/-0um, Concertricity: ≤0.5um	125.0um, Concertricity: ≤3.0um
	125.3+1/-0um, Concertricity: ≤1.0um	125.3+1/-0um, Concertricity: ≤0.5um	127.0um, Concertricity: ≤3.0um
	125.5+1/-0um, Concertricity: ≤1.0um	125.5+1/-0um, Concertricity: ≤0.5um	128.0um, Concertricity: ≤3.0um
	126.0+1/-0um, Concertricity: ≤1.0um	126.0+1/-0um, Concertricity: ≤0.5um	

**Order Information:**

<b>Item</b>	<b>Connector Description</b>	<b>Item</b>	<b>Connector Description</b>
	<b>PC/UPC/APC</b>		<b>PC/UPC/APC</b>
<b>Connector Singlemode 9/125</b>	ST	<b>Connector Multimode (50/125 or 62.5/125)</b>	ST
	SC		SC
	FC		FC
	LC		LC
	MU		MU
	MTRJ(female)		MTRJ(female)
	MTRJ(male)		MTRJ(male)
	DIN		