

**Specification:**

Type/Performance	SM(APC Polish)		MM (UPC / Flat Polish)	
	Standard	Elite Low Loss	Standard	Elite Low Loss
<b>Maximum Insertion Loss</b>	≤ 0.75dB	≤ 0.35dB	≤ 0.60dB	≤ 0.35dB
<b>Return Loss</b>	≥ 50dB		N/A	
<b>Operating Temperature</b>	-40°C to 80°C		40°C to 80°C	
<b>Test Wavelength</b>	1310nm		850nm	

**Order Information:**

Connector #1	Polishing	Connector #2	Polishing	Cable Fiber	Diameter	Mode type	Length	Remark
1:SC	P:PC	1:SC	P:PC	1:simplex	1:0.9mm	6:62.5/125	1:1M	A:Armoved
2:ST	U:UPC	2:ST	U:UPC	2:duplex	2:2.0mm	5:50/125	2:2M	
3:FC	A:APC	3:FC	A:APC	3:4fibers	3:3.0mm	9:9/125		
4:LC		4:LC		4:6fibers		1:50/125OM3		
5:MTRJ		5:MTRJ		5:8fibers		2:50/125OM4		
6. MU		6. MU		6:12fibers				
7:SMA		7:SMA		7:24fibers				
8:MPO		8:MPO		8:48fibers				
9. DIN		9. DIN						
10.D4		10.D4						