

**Specification:**

Mode	SM			MM	
	PC	APC	UPC	PC	UPC
Polishing					
Insertion Loss	$\leq 0.3\text{dB}$	$\text{UPC} \leq 0.3\text{dB}$	$\text{APC} \leq 0.3\text{dB}$	$\text{APC} \leq 0.3\text{dB}$	$\text{APC} \leq 0.3\text{dB}$
Return Loss	$\text{PC} \geq 52\text{dB}$	$\text{APC} \geq 65\text{dB}$	$\text{UPC} \geq 55\text{dB}$	$\text{PC} \geq 35\text{dB}$	$\text{UPC} \geq 35\text{dB}$
Exchangeability	$\leq 0.2\text{dB}$				
Salt Spray	$\leq 0.2\text{dB}$				
Vibration	$(550\text{Hz } 1.5\text{mm}) \leq 0.1\text{dB}$				
Apex Offset	$0\mu\text{m} \leq 50\mu\text{m}$				
Radius of Curvature	$7\text{mm} \leq 25\text{mm}$				
Humidity	$(+25+65 \text{ 93 R.H. } 100 \text{ hours}) \leq 0.2\text{db}$				
Cable Type	Type Simplex, Duplex, Fan-Out				
Connector Type	LC, SC, FC, ST, MU, MPO, MTRJ, DIN, SMA, FDDI				