

Specification:

Type	Single mode (APC polish)		Single mode (PC polish)		Multi mode (PC polish)	
Fiber count	4,8,12, 24 etc.		4,8,12, 24 etc.		4,8,12, 24 etc.	
Fiber type	G652D,G657A1 etc.		G652D,G657A1 etc.		OM1,OM2,OM3 etc.	
Maximum Insertion Loss	Elite	Standard	Elite	Standard	Elite	Standard
	Low Loss		Low Loss		Low Loss	
	≤0.35 dB	≤0.70 dB	≤0.35 dB	≤0.70 dB	≤0.35dB	≤0.50dB
Return Loss	≥55 dB		≥45 dB		≥20 dB	
Durability	≥200 times		≥200 times		≥200 times	
Operating Temperature	-40°C ~ +80°C		-40°C~ +80°C		-40°C ~ +80°C	
Test Wavelength	1310nm		1310nm		850nm	

Ordering information:

Connector PIN	Hook Color	Boot Type	Fiber Type	Cable number	Ferrule	Length
Male	Biege Black Green Yellow	Bare fiber short Ruggedized ribbon cable Bare fiber long 90 degree	9/125um SM 50/125um MM 62.5/125um MM OM3 OM4	4-fiber 8-fiber 12-fiber 16-fiber 24-fiber	PC APC	Customized
Female						