

Specification:

Type	Multimode Standard Fibre Splitters
Coupling Ratio (%)	50/50
Excess Loss (Typical) (dB)	0.5 (0.8)*
Max. Insertion Loss (dB)	3.5 (4.0)*
Uniformity (Max.) (dB)	0.6
Directivity (dB)	>40dB
Operating Wavelength (nm)	600-1600
Central Wavelength (nm)	850 or 1310 or 1550
Operating Temperature	-40° C - 85° C
Fibre Type	Corning Multimode 50/125, 62.5/125 Fibre
Fibre Pigtail Length (m)	1 or Custom on Request
Port Configuration	1x2 or 2x2
Package Dimension	Package A,B,C

*For 50/125 um, 62.5/125 um Fibre, 50% coupling ratio

Type	Multimode 1x3, 1x4 True Fusion Splitters	
Port Configuration	1x3	1x4
Max. Insertion Loss (dB)	6.0 (6.5)*	7.2 (7.6)*
Uniformity (Max.) (dB)	1.2	1.2
Directivity (dB)	>40dB	
Operating Wavelength (nm)	600-1600	
Central Wavelength (nm)	850 or 1310	
Operating Temperature	-40° C - 85° C	
Fibre Type	Corning Multimode 50/125, 62.5/125, 100/140 Fibre	
Fibre Pigtail Length (m)	1 or Custom on Request	
Package Dimension	Package B,C	